

**Material Safety Data Sheet**

Product Name: Rubber Clear RC-8420

Date: January 1, 2012

1. MANUFACTURER FOR : ALSA Corporation  
1213 E. 58th Place  
Los Angeles, CA 90001

EMERGENCY PHONE : 800-535-5053 / 352-323-3500  
INFORMATION PHONE : (323)581-5200

**2. COMPOSITION/INFORMATION ON INGREDIENTS.**

Substances presenting a health hazard within the meaning of the Dangerous Substances Directive.

<b>EINECS-No.</b>	<b>Names</b>	<b>CAS Num</b>	<b>Conc.</b>
215-535-7	xylene, mixture of isomers	1330-20-7	1 - 2.5
202-849-4	Ethyl benzene	100-41-4	0.1 -0.5
204-658-1	n-butyl acetate	123-86-4	25 - 50
200-661-7	propan-2-ol; isopropyl alcohol	67-63-0	2.5 - 10
	Resin	Non-hazardous	25 - 50

**3. HAZARDS IDENTIFICATION OF THE PREPARATION.**

**Danger classification :** Xn Harmful

- 11 Highly Flammable.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapors may cause drowsiness and dizziness.

**4. FIRST AID MEASURES.**

**General:**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation:**

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

**Eye contact:**

Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

**Skin contact:**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do **NOT** use solvents or thinners.

**Ingestion:**

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do **NOT** induce vomiting.

**Material Safety Data Sheet**

Product Name: Rubber Clear RC-8420

Date: January 1, 2012

5. **FIRE-FIGHTING MEASURES.**

**Extinguishing media:** recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray  
not to be used : water jet.

**Recommendations:** Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with care. Do not allow run-off from fire fighting to enter drains or water courses.

6. **ACCIDENTAL RELEASE MEASURES.**

Exclude sources of ignition and ventilate the area. Avoid breathing vapors. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7. **HANDLING AND STORAGE.**

**Handling.**

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid inhalation of dust, particulates and spray mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Smoking, eating and drinking should be prohibited in application area. For personal protection see Section 8.

Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws.

**Storage.**

Although the storage and use of this product is not subject to specific statutory requirements, observation of the principles of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations as appropriate will be seen as good industrial practice in meeting the general duties of the Health and Safety at Work Act.

Observe label precautions. Store between 10 and 25 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep away from sources of ignition. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. **EXPOSURE CONTROLS/PERSONAL PROTECTION.**

**Engineering Measures.**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapor below the OEL, suitable respiratory protection must be worn.

**Exposure Limits.**

Occupational exposure limit for:

EINECS-No.	Names	CAS Num	STEL	LTEL
215-535-7	xylene, mixture of isomers	1-330-20-7	150ppm	100 ppm
204-658-1	n-butyl acetate	123-86-4	200ppm	150 ppm
200-661-7	propan-2-ol; isopropyl alcohol	67-63-0	500ppm	400 ppm
202-849-4	Ethyl benzene	100-41-4	125ppm	100 ppm

**Protection.**

**Respiratory protection:**

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

**Hand protection:**

For prolonged or repeated handling, use Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

**Eye protection:**

Use safety eyewear designed to protect against splash of liquids.

**Skin protection:**

Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

9. **PHYSICAL AND CHEMICAL PROPERTIES.**

Physical state	Viscous	
flash point	54 °F	
specific gravity	1.05	
vapor density	Heavier than air	DIN
lower explosion limit	1.0	DIN
solubility in water	Not Soluble	
boiling range	180-284°F	

10. **STABILITY AND REACTIVITY.**

Stable under recommended storage and handling conditions (See section 7). When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. **TOXICOLOGICAL INFORMATION.**

There are no data available on the preparation itself. The preparation has been assessed following the conventional methods of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Chapter 2 and 15 for details. Exposure to component solvents vapors concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

**Material Safety Data Sheet**

Product Name: Rubber Clear RC-8420

Date: 07-12-07

12. **ECOLOGICAL INFORMATION.**

The product should not be allowed to enter drains or water courses.

13. **DISPOSAL CONSIDERATIONS.**

Do not allow into drains or water courses.

Wastes and emptied containers should be deposited according to the official rules.

**Code of waste Waste Designation:**

080111 waste paint and varnish containing organic solvents and other dangerous substances

14. **TRANSPORT INFORMATION.**

Transport only in accordance with ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

**ADR/RID Class:** 3 (flammable liquid)

Tremcard:

UN-No: 1263

Transport document name: Paint and paint related material

Packaging group: II

**IMDG Class:** 3 (flammable liquid)

EmS: F-E, S-E

UN-No: 1263

PAINT shipping name: PAINT & PAINT RELATED MATERIAL

Packaging group: II

marine pollutant: n.a.

**ICAO/IATA Class:** 3 (flammable liquid)

UN No: 1263

Proper shipping name: paint and paint related material

Packaging group: II

15. **REGULATORY INFORMATION.**

In accordance with requirements of the Classification Packaging and Labeling of Dangerous Substances Regulations.

The product is labeled as follows:

**Danger classification:**

**Xn Harmful**

**Contains:**

**Xylene, ethyl benzene**

**R-phrases:**

**11** Highly Flammable

**66** Repeated exposure may cause skin dryness or cracking.

**67** Vapors may cause drowsiness and dizziness.

**S-phrases:**

**24** Avoid contact with skin.

**38** In case of insufficient ventilation, wear suitable respiratory equipment.

**51** Use only in well-ventilated areas.

**23** Do not breathe vapor.

**Material Safety Data Sheet**

Product Name: Rubber Clear RC-8420

Date: January 1, 2012

**US FEDERAL REGULATIONS:**

**SARA 313: XYLENE, ETHYL BENZENE**

**SARA 311/312: ACUTE (YES) CHRONIC (NO) FIRE (YES) PRESSURE (NO) REACTIVITY (NO)**

**PROP 65: ETHYL BENZENE**

**TSCA: ALL OF THE INGREDIENTS ARE LISTED.**

**SECTION 16: OTHER INFORMATION**

**HMS**

**HEALTH: 2**

**FLAMMABILITY: 3**

**REACTIVITY: 0**

**PROTECTION: H**

**DISCLAIMER:**

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT, HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN. THIS MATERIAL SAFETY DATA SHEET WAS PREPARED TO COMPLY WITH THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200, AND SUPERSEDES ANY PREVIOUS INFORMATION, PREVIOUSLY DATED SHEETS ARE INVALID AND UNAPPLICABLE.