

ALSA REFINISH LLC,  
MATERIAL SAFETY DATA SHEET

SECTION I

PRODUCT NAME OR NUMBER: EASY CHROME BASECOAT	
MANUFACTURER'S NAME: ALSA REFINISH LLC,	Only in the Event of CHEMICAL EMERGENCY, Spill, Leak, Fire, Exposure, or Accident Call: (323) 515-1100 Also Refinish LLC, (352) 323-3500 InfoTrac
ADDRESS 1213 E. 58 <sup>th</sup> PL. Los Angeles, CA 90001	
HAZARDOUS MATERIALS DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO. (49 CFR172.101): RESIN COMPOUND	
ADDITIONAL HAZARD CLASSES: Not regulated.	
CHEMICAL FAMILY: Water Soluble Polymers	FORMULA: Base coat

SECTION II - INGREDIENTS

CAS REGISTRY NO.	% W	CHEMICAL NAME(S)
7732-18-5	100	water
63148-65-2	12	Polyvinyl butyral resin

All components of this material are on or exempt from the US TSCA Inventory

SECTION III - PHYSICAL DATA

BOILING POINT: >212°F °C		SPECIFIC GRAVITY (H <sub>2</sub> O = 1):	1.07-1.09	VAPOR DENSITY (AIR =1)	Water
VAPOR PRESSURE: @ °F °C [ ] mmHg [ ] psi		PERCENT VOLATILE BY WT.: VOC: #/gallon	50-55 0.009	EVAPORATION RATE (Butyl Acetate = 1):	Water
SOLUBILITY IN WATER:	100%	PERCENT SOLID BY WEIGHT:	45-50	pH = (neat) Approx.	7-9
APPEARANCE AND ODOR: Viscous white liquid, Mild Odor			IS MATERIAL (LIQUID) SOLID GAS PASTE POWDER		

SECTION IV - FIRE AND EXPLOSION HAZARD DATE

FLASH POINT: None (Method used -)ASTM D-92 °F °C	FLAMMABLE LIMITS	LEL	UEL
		N/A	N/A
EXTINGUISHING MEDIA:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER FOG			
SPECIAL FIRE FIGHTING PROCEDURES: None			
UNUSUAL FIRE AND EXPLOSION HAZARDS: None			

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: SKIN: Prolonged or repeated contact may cause some irritation	THRESHOLD LIMIT VALUE: Undetermined
PRIMARY ROUTES OF ENTRY: Inhalation [ X ] Skin Contact [ X ] Other (Specify) EYE & INGESTION	
EYES: flush with plenty of water for 15 minutes. INHALATION: Remove to fresh air. SKIN: Wash with soap and water.	
INGESTION: Should be removed from stomach by induced vomiting or aspiration. In all cases, seek medical attention.	
EMERGENCY AND FIRST AID PROCEDURES: If any ill effects occur from the use of this product, seek medical attention.	

PAINTSHIELD 5720  
SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID: Excessive heat.
	STABLE	X	
INCOMPATIBILITY: STRONG OXIDIZING AGENTS			
HAZARDOUS DECOMPOSITION PRODUCTS: May produce oxides of carbon or nitrogen.			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike and contain spill with inert material (sand, earth, etc). Transfer liquid and solids to containers for recovery or disposal. Spill emulsion is very slippery. Avoid falls.
WATER DISPOSAL METHOD: In accordance with state, local and federal requirements

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NIOSH approved if needed.		
VENTILATION	LOCAL EXHAUST: NOT REQUIRED	SPECIAL:
	MECHANICAL: NOT REQUIRED	OTHER:
PROTECTIVE GLOVES: Impervious.	EYE PROTECTION: SAFETY GLASSES	
OTHER PROTECTIVE EQUIPMENT: Chemical apron, safety shower.		

SECTION IX - SPECIAL PRECAUTION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in cool dry place. Avoid freezing, minimize contact with air to prevent bacterial growth.	
OTHER PRECAUTIONS: NONE	
	DATE ISSUED: December 31, 2016

Information presented herein has been compiled to be dependable and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for him/herself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.