



ALSA CORPORATION  
2311 Roscomare Rd, Los Angeles, CA 90077, USA  
Emergency Contact: +1 (310) 804-9977  
Website: alsacorp.com

# SAFETY DATA SHEET (SDS)

## Easy Chrome FX

Decorative chrome coating aerosol - branded ALSA format with full multi-section content

### 2. Hazard Identification



Flammable



Irritant

Signal Word: DANGER

GHS Classification: Flammable Aerosol Category 1; Pressurized Container; Skin Irritation Category 2; Eye Irritation Category 2A; STOT SE Category 3

### 1. Identification

Product Identifier: Easy Chrome FX

Recommended Use: Decorative chrome coating for metal, ABS plastic, prepared surfaces, trim, and appearance restoration.

Supplier: ALSA Corporation, 2311 Roscomare Rd, Los Angeles, CA 90077, USA.

Emergency Phone: +1 (310) 804-9977

Document Control: Issue Date: March 2026 | Revision: 1 | Prepared under GHS/OSHA HazCom 2012 aligned format

### 3. Composition / Information on Ingredients

Ingredient	CAS Number	Approx. %	Notes
Propane (LPG)	74-98-6	60	Propellant
Ethyl Acetate	141-78-6	8	Solvent
Butyl Acetate	123-86-4	8	Solvent
Glycol Ether (Diethylene glycol monobutyl ether)	112-34-5	3	Co-solvent
Polyurethane Resin	Proprietary	15	Binder / resin
Aluminum Pigment	7429-90-5	6	Metallic pigment

### 4. First-Aid Measures

Inhalation: Move person to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms persist.

Skin Contact: Wash thoroughly with soap and water. Remove contaminated clothing and wash before reuse. Get medical attention if irritation develops.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Get medical attention if irritation persists.

Ingestion: Rinse mouth. Do not induce vomiting. Seek medical attention immediately.

Most Important Symptoms: Eye irritation, skin irritation, dizziness, drowsiness, respiratory irritation, and discomfort after overexposure to vapors.

## 5. Fire-Fighting Measures

- Suitable extinguishing media: foam, dry chemical, or carbon dioxide (CO<sub>2</sub>).
- Do not use a direct water jet, which may spread burning material.
- Containers may rupture or explode when exposed to heat because the product is a pressurized aerosol.
- Firefighters should wear full protective equipment and self-contained breathing apparatus.

## 6. Accidental Release Measures

- Eliminate all ignition sources and ventilate the area.
- Wear suitable gloves, eye protection, and respiratory protection where ventilation is inadequate.
- Prevent spilled material from entering drains, waterways, or soil.
- Absorb liquid residue with inert material such as sand, vermiculite, or earth and place in suitable containers for disposal.

## 7. Handling and Storage

- Use only in well-ventilated areas.
- Do not spray on open flame or other ignition source.
- Do not pierce or burn, even after use.
- Store below 50 C / 122 F, away from direct sunlight, heat, sparks, and oxidizing materials.
- Keep containers tightly closed when not in use.

## 8. Exposure Controls / Personal Protection

Engineering Controls: Use local exhaust or general ventilation sufficient to maintain vapor concentration below occupational exposure limits.

Respiratory Protection: Organic vapor respirator where engineering controls are insufficient.

Hand Protection: Nitrile gloves or equivalent chemical-resistant gloves.

Eye Protection: Safety goggles or safety glasses with side shields.

Skin / Body Protection: Protective clothing as needed to avoid repeated contact.

## 9. Physical and Chemical Properties

Appearance: Silver aerosol

Odor: Solvent-like

Flash Point: -20 C

Solubility: Insoluble in water; soluble in organic solvents

Physical State: Aerosolized liquid coating

## 10. Stability and Reactivity

- Stable under recommended storage and handling conditions.
- Avoid heat, open flames, sparks, static discharge, and strong oxidizing agents.
- Hazardous decomposition products may include carbon oxides and irritating fumes during combustion.

## 11. Toxicological Information

- May cause irritation to skin, eyes, and respiratory tract.
- Overexposure may cause headache, dizziness, drowsiness, and central nervous system depression.

- Repeated skin contact may cause dryness or cracking.

## 12. Ecological Information

- Avoid release to the environment.
- Volatile organic components may contribute to air pollution.
- Prevent discharge into drains, waterways, and soil.

## 13. Disposal Considerations

- Dispose of contents and container in accordance with local, regional, national, and international regulations.
- Do not puncture, crush, or incinerate empty aerosol containers.

## 14. Transport Information

Field	Information
UN Number	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1
Packing Group	Not applicable
Special Precautions	Protect from heat and physical damage; read SDS before handling

## 15. Regulatory Information

- Prepared to align with GHS and OSHA Hazard Communication Standard requirements.
- User remains responsible for compliance with all applicable storage, transportation, workplace, and environmental regulations.

## 16. Other Information

- ALSA Corporation revision reference: Issue Date: March 2026 | Revision: 1 | Prepared under GHS/OSHA HazCom 2012 aligned format.
- The information is believed to be accurate as of the issue date and is intended for safe handling, use, processing, storage, transportation, disposal, and release response.